CLAIMS

5

10

1. A fuel cell comprising:

a fuel electrode, an oxygen electrode and a proton conductor film layer disposed between the fuel electrode and the oxygen electrode;

at least one of the fuel electrode and the oxygen electrode comprising an electrode material composed of powders of a carbonaceous material coated on a surface thereof with a proton conductor material wherein the proton conductor material comprises a carbon-based material substantially composed of carbon forming a matrix structure that has one or more proton dissociative groups introduced to the matrix structure.

- 2. The fuel cell according to claim 1 wherein the carbonaceous material of the powders comprises a carbonaceous material formed of fibers.
- 15 3. The fuel cell according to claim 2 wherein the carbonaceous material formed of fibers is selected from the group consisting of carbon nano-tubes, a fibrous graphite material and mixtures thereof.
- 4. The fuel cell according to claim 1 wherein at least one of the fuel electrode and the oxygen electrode comprises a catalyst having a metal component.
 - 5. The fuel cell according to claim 4 wherein the metal component is selected from the group consisting of platinum, platinum alloy and combinations thereof.

25

- 6. The fuel cell according to claim 1 wherein the proton conductor film layer comprises a material similar to the proton conductor material.
- 7. The fuel cell according to claim 1 wherein the carbon-based material of the proton conductor material is selected from the group consisting of carbon clusters, carbon nano-tubes and mixtures thereof.

5

10

15

8. A method for the preparation of a fuel cell including a fuel electrode, an oxygen electrode and a proton conductor material disposed therebetween comprising the steps of:

providing a carbonaceous material in a powder form;

mixing the carbonaceous material with a solvent that contains a proton conductor wherein the proton conductor comprises a carbon-based material substantially composed of carbon and one or more proton dissociate groups introduced to the carbon-based material;

coating a surface of the carbonaceous material with the proton conductor; and

forming at least one of the fuel electrode and the oxygen electrode with the carbonaceous material.

- 9. The method according to claim 8 wherein the carbon-based material of the proton conductor comprises a matrix structure into which the proton dissociative groups are introduced.
- The method of claim 8 wherein the carbonaceous material comprises
 a carbonaceous material composed of carbon fibers.
 - 11. The method of claim 8 wherein the carbon-based material is selected from the group consisting of carbon clusters, carbon nano-tubes and mixtures thereof.

25